

Blixer® 8



8 Qt.

A SALES FEATURES
Blixer 8 is designed to prepare texture-modified meals with either raw and cooked ingredients in a minimum of time.

B TECHNICAL FEATURES
 Blixer 8. 3-phase. Power 3 HP. 2 speeds. Pulse function. 8 Qt. stainless-steel bowl with 2 handles. Bowl-base blade assembly with 2 detachable fine serrated blades included. Scraper arm and lid wiper included. 5 to 25 portions (7 oz.) and more.
 Select your options at the back page, **F** part.

C TECHNICAL DATA	
Output power	3 HP
Electrical data	208-240V/60/3
Speeds	1800 and 3600 rpm
Dimensions (HxLxW)	23 15/16" x 21 1/2" x 12 7/16" - Cube 3.73
Rate of recyclability	95%
Net weight	110 lbs
Nema #	L15-20P
Reference	BLIXER 8 - 208-240V/60/3

D Number of 7 oz portions :	5 to 25 portions
Quantity processed per operation	2 to 11 lbs

E PRODUCT FEATURES / BENEFITS

- MOTOR BASE**
- Direct drive induction motor (no belt) for intensive use.
 - Power 3 HP.
 - Stainless steel motor shaft.
 - Flat, easy-clean motor base.
 - IP65 control panel with flush buttons.
 - Magnetic safety and motor brake.
 - **2 speeds : 1800 and 3600 rpm**
 - Pulse function for a better cut precision.

- CUTTER FUNCTION**
- 8 Qt. stainless-steel bowl with 2 handles for a better grip.
 - Central bowl locking system for easy assembly.
 - Bowl-base blade assembly with 2 fine serrated blades to ensure a perfectly uniform consistency, even when processing small quantity.
 - Transparent lid to enable user to monitor processing.
 - Opening in centre of lid for adding liquid or dry ingredients during processing.
 - **Transparent lid with bowl scraper** to improve the end-product consistency and **with a lid wiper** to enable user to monitor processing.
 - **Opening in center of lid** for adding liquid or dry ingredients during processing.

- INCLUDED ACCESSORIES**
- Stainless steel fine serrated blade assembly (2 blades)
 - Scraper arm and lid wiper

STANDARDS
 ETL electrical and sanitation Listed/ cETL (Canada)

Blixer® 8

F OPTIONAL ATTACHMENTS

- 2 Blade Fine Serrated Edge Stainless Steel Adjustable Blade Assembly - Ref. 27377
- Lid Assembly with seal - Ref. 59319
- Complete Bowl Assembly - Ref. 59264

G ELECTRICAL DATA

208-240V/60/3 – delivered with cord and plug.

